







ASIAN HOLLOW BLOCK

– Concrete Blocks –



Special Features:

- Manufactured in 100% Automated Plant with technology from Germany
- Superior finish
- · Excellent sound and thermal insulation
- · Lower density and weight
- Pre-cured
- Minimum breakage and wastage

Where to be used:

Where to be used: Fair Face Walls | Partitioning Walls | Load Bearing Walls | Boundary Walls | Decorative Application

Colour Range:





Grev

Customized

Specifications:

Parameters	Dimensions
Hollow Block (in)	4/6/8
Length (mm)	390
Height (mm)	190
Thickness (mm)	100 / 150 / 200
Blocks/m²	13.49
Compressive Strength (N/mm²)	≥ 7.5
Blocks/sqft	1.25

8" Hollow Blocks






6" Hollow Blocks





4" Hollow Blocks



Advantages:

- Rapid Execution of Work:
 Asian Hollow Blocks are lighter and of uniform size. This facilitates rapid execution.
- Increase in Floor Area:
 Option to build thinner walls helps save space and increase floor area.
- Reduces Construction Cost: Asian Hollow Blocks helps save construction material and reduces construction cost.
- Better Insulation: Offers great insulation against sound, heat and dampness.
- More Durable: Asian Hollow Blocks withstands atmospheric turmoil and requires no protective covering.
- Bonding of Mortar & Plaster: Rough surface provides good bonding of mortar and plaster.
- Cost-Effective: The block's durability and great strength reduce maintenance cost.

ASIAN CONCRETO PVT. LTD.







INDIA SALES OFFICE:

Plot No. 84, Palm Paradise, Ramgarh Taal, Gorakhpur, UP, India Phone: +91-8127585858

NEPAL SALES OFFICE:

1st Floor, ShriPri Home, Kalikasthan - 29, Kathmandu, Nepal Phone: +977-9802711199

FACTORY:

Ramgram - 16 Nawalparasi, Nepal. Phone: +977-9802711199