

vehicles from grazing themselves against the edge of a pavement or carriageway.

The kerb stones have a sloping back profile which provides this protection. Their inherent shape also allows road rollers to operate right against the edge of pavements without damaging the kerb surface.

provide a soft-edge restraint to the kerb stone while maintaining a 90° angle with the ground. Due to its smooth, curved edge, Bull-Nosed Kerb Stone is suitable for a variety of applications with the aim of providing definition. Bull-Nosed Kerb Stone is apt for driveways in residential schemes and commercial applications where strength and durability are essential.



Special Features:

- · High dimensional accuracy
- Extreme strength
- Flawless finish
- Low water absorption

Advantages:

- Remarkable longevity and value retention
- Fewer joints, aesthetically pleasing
- Reduced blackening
- Cost-effective
- Low maintenance

Where to be used:

Roadways | Pathways | Bordering Pathways | Bordering Steps | Bordering Flowerbeds

Colour Range:





Grov

Customized

Specifications:

For both Half-Battered Kerb Stone & Bull-Nosed Kerb Stone

Parameters	Dimensions
Length (mm)	250/300/300
Breadth (mm)	200 / 200 / 165
Height (mm)	380 / 350 / 325
Kerbs/rm	4 / 3.33 / 3.33
Kerbs/rft	1.22 / 1.02 / 1.02
Compressive Strength (N/mm²)	≥ 20

ASIAN CONCRETO PVT. LTD.







INDIA SALES OFFICE:

Plot No. 84, Palm Paradise, Ramgarh Taal, Gorakhpur, UP, India Phone: +91-8127585858

NEPAL SALES OFFICE:

1st Floor, ShriPri Home, Kalikasthan - 29, Kathmandu, Nepal Phone: +977-9802711199

FACTORY:

Ramgram - 16 Nawalparasi, Nepal. Phone: +977-9802711199